240

Dresser Atlas

Geophysical Survey Exp. 240

ELECTRIC LOG

COMPANY: Jackson County Rural Electric
Cum Cleary Stockdale Center Inc. 240

WELL: Stock Well #1

FIELD: Stockdale

COUNTY: Jackson STATE: Mississippi

COMPANY: Sec. 17, T.7S., R.1E.

Other Services

Sec. 17 Twp. 7S Rge. 1E

Elev.: K.B. 45 D.F. G.L.

Date: 1-10-1964

Type Well: Oil

Depth-Driller: 892'

Depth-Logger: 892'

Bottom Log Interval: 892'

Top Log Interval: 0'

Casing-Driller: 8 5/8" @ 24'

Casing-Logger: 24'

Bit Size: 7 7/8"

Type Fluid in Hole: Water

Dens. lb/gal: 8.4

Visc. sec: 28

pH: 7

Fluid Loss cc/30 min: N.A.

Source of Sample: Circ. Tank

Rm @ Meas. Temp.: .5 @ 70°

Rmf @ Meas. Temp.: .5 @ 70°

Rmc @ Meas. Temp.: .5 @ 70°

Source Rmf / Rmc: Calc. / Calc.

Rm @ BHT: .5 @ 100°

Time Since Circ.: 24 hrs.

Max. Rec. Temp.: 100°

Equip. No.: 1

Location: Hwy. 63

Recorded by: Hollis Hawkins

Witnessed by: Mr. Ed Cleary

SPONTANEOUS POTENTIAL millivolts	Depths	RESISTIVITY ohms m²/m
- 10 MV +		SHORT NORMAL AM = 16" 50 100
		LONG NORMAL AM = 64" 50 100
	100	
	200	
	300	
	400	
	500	
	600	
	700	
	800	
	Est. Pay	
	P-1 Hydro	
	892	50 OHMS

TD 904'

SPONTANEOUS POTENTIAL millivolts	DEPTHS	RESISTIVITY ohms m²/m
- 10 MV +		SHORT NORMAL AM = 16" 0 50 100
		LONG NORMAL AM = 64" 0 50 100